

TEC BORD

Acrylic Gypsum Board Jointing & Wall Putty

TEC BORD is a water-based, multi-purpose acrylic putty for gypsum board joints, formulated to provide an excellent foundation for a perfect paint finish. It dries quickly, leaving behind an ultra-smooth surface that is ready for laying the top coat.

SCOPE OF USE

- Interior wall and ceiling surfaces prior to painting.
- Gypsum board joints and general wall/masonry putty finishing.

ADVANTAGES

- Water resistant finish.
- High coverage.
- Easy to apply.
- Eco-friendly formulation.
- Low odor.

TECHNICAL DATA

This product's technical values are not printed on the supplied packaging and are pending confirmation from PRO-TEC's Technical / R&D Department based on lab testing. Do not publish or distribute until verified and completed.

TYPE	Water-based, multi-purpose acrylic putty
PACKAGING SIZE	25 kg

APPLICATION GUIDE

1. Surface Preparation

The surface to be treated must be clean, dry, and free from leakage, loose oil paint, dirt, dust, grease, oils, soap, wax and any other contaminants. Remove any peeling paint and sand the area smooth, feathering the edges with adequate sandpaper.

2. Substrate Condition

New plaster or masonry surfaces must be allowed to cure prior to application, and the surface plaster must be allowed to dry in good condition before the putty is applied.

3. Repairs Before Application

Repair any cracks in base elements, leakage or previous surface problems before painting. Ensure non-structural cracks are filled with cement filler before proceeding, and wash putty depths/cracked areas thoroughly with drinking water as needed.

4. Finishing

Once dry, sand smooth with fine sandpaper and clean the surface thoroughly before applying paint.

PACKAGING & STORAGE

- Supplied in 25 kg packaging.

HEALTH, SAFETY & CAUTIONS

Water-based acrylic putty; avoid prolonged skin/eye contact and ensure adequate ventilation during sanding.

- Avoid prolonged contact with eyes and skin.
- Use appropriate PPE (gloves, eye protection) during application.
- Ensure good ventilation during use, especially in confined interior spaces.
- Refer to the product Material Safety Data Sheet (MSDS) for complete health and safety guidance.
- Keep out of reach of children. Store away from sources of heat and ignition.

PRO-TEC

Trust our chemistry

Disclaimer:

Pro-Tec makes every effort to ensure that any advice, suggestions, or information it provides is reliable and accurate. It cannot assume any direct or indirect liability arising from the use of its goods since it has no direct or continuous control over where or how its products are used, whether or not in line with any advice, specification, suggestion, or information provided by us. Pro-Tec has the right, at its discretion, to alter any of the parameters included in the technical data sheets without previous notice. Hard copies of the technical data sheets are printed once or twice a year, while our technical data sheets are constantly updated as a result of R&D advancements and fresh third-party testing; please visit our website for the most recent updates.

Note: The information included on this Technical Data Sheet is the sole property of Pro-Tec. The unauthorized disclosure, use, dissemination, or copying (either whole or partial) of this data sheet or any information it contains is prohibited and subject to legal pursuit.