

TEC ROOF COAT

Acrylic Elastomeric Roof Waterproofing Coating

TEC ROOF COAT is a cold-applied, single-pack elastomeric acrylic waterproof coating material based on a special pigmented aqueous synthetic resin, providing a seamless waterproofing layer for roofs and other exposed surfaces.

SCOPE OF USE	ADVANTAGES
- Waterproofing layer on all types of new and old roofs — concrete and masonry, asphalt. - Wooden surfaces, tiles, bricks and stone. - Galvanized steel, corrugated steel and Kirby sheet steel. - Plastered walls.	- High performance, cold-applied single-pack system. - Strong adhesion to a wide range of substrates. - Elastomeric waterproofing protection. - European quality standard.

TECHNICAL DATA

FINISH	Matte to eggshell
COLOUR	According to shade card
PRODUCT WEIGHT	Approx. 1.1 kg/liter (depending on color)
VOLUME SOLIDS	Approx. 50% (depending on color)
RECOMMENDED DFT	0.5 mm
THEORETICAL COVERAGE	750 microns WFT is approximate 0.8kg per m2
DRYING TIME	Touch dry: 1–2 hours; Hard dry: 12–14 hours
FLAMMABILITY	Non-flammable

APPLICATION GUIDE

1. Product Overview

TEC ROOF COAT is a cold-applied, single-pack, elastomeric acrylic waterproof coating material based on a special pigmented aqueous synthetic resin.

2. Intended Use

Apply as a waterproofing layer on new and old roofs of concrete and masonry, asphalt, wooden surfaces, tiles, bricks, stone, galvanized/corrugated/Kirby sheet steel, and plastered walls.

PACKAGING & STORAGE

- Supplied in 25 kg packaging.

HEALTH, SAFETY & CAUTIONS

Non-flammable, water-based acrylic coating; avoid prolonged skin/eye contact and ensure adequate ventilation during application.

- Avoid prolonged contact with eyes and skin.
- Use appropriate PPE (gloves, eye protection) during application.
- Ensure good ventilation during use, especially in confined interior spaces.
- Refer to the product Material Safety Data Sheet (MSDS) for complete health and safety guidance.
- Keep out of reach of children. Store away from sources of heat and ignition.

PRO-TEC

Trust our chemistry

Disclaimer:

Pro-Tec makes every effort to ensure that any advice, suggestions, or information it provides is reliable and accurate. It cannot assume any direct or indirect liability arising from the use of its goods since it has no direct or continuous control over where or how its products are used, whether or not in line with any advice, specification, suggestion, or information provided by us. Pro-Tec has the right, at its discretion, to alter any of the parameters included in the technical data sheets without previous notice. Hard copies of the technical data sheets are printed once or twice a year, while our technical data sheets are constantly updated as a result of R&D advancements and fresh third-party testing; please visit our website for the most recent updates.

Note: The information included on this Technical Data Sheet is the sole property of Pro-Tec. The unauthorized disclosure, use, dissemination, or copying (either whole or partial) of this data sheet or any information it contains is prohibited and subject to legal pursuit.